

# Impact-D 161A




## Features

The Impact-D 161A is a compact, DIN Rail mountable, low power embedded system, utilising the superb Intel Skylake Mobile processing technology.

Key features:-

- 3 year warranty
- 15 Year life cycle
- Din Rail mount

## Dimensions



## Impact-D 161A

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

### Specifications

Hardware Specification	CPU: Intel I core i5-6300U SOC Main memory: Dual DIMM 4GB SODIMM DDR3L (max: 16GB) LAN: Dual integrated 10/100/1000	Mechanical	Design: Rugged compact embedded design Cooling: Fanless design Construction: Extruded Aluminium Colour: Black Dimension: 80 x 200 x 145mm (W x H x D) Gross Weight: 1.3kg
BIOS	AMI	Environmental Operation	Acoustic noise: Near silent operation Operating Temperature: 0°C to 60°C Humidity: 0 to 60% non-condensing
Display	HDMI: 4096x2160 @ 24Hz VGA: 1920x1200 @ 60Hz	Environmental Storage	Temperature: -40°C to 75°C Humidity: 5% to 95% RH Non-condensing
Storage	1 x 2.5" SSD 1 x mSATA Colay mPCIe	Certifications	CE/UKCA
System Expansion	2 x Full size mPCIe (1 with SIM)		
Supported O/S	Windows 7 Pro / Windows 10 Pro / Windows 10 IoT / Linux		
External Interfaces	2 x USB 3.0 Front 2 x USB 2.0 Front 2 x RJ45 LAN 2 x RS232/422/485 1 x HDMI 1 x VGA		
LED's and Switches	Power (PC on LED) Hard disk access LED ATX system control switch		
Main board Power options	Supports DC input: 9-32VDC on Phoenix connector		

### Rear I/O plate

